

INDUSTRIAL COMPONENT DATA

PSR-PC52-1NO-1NC-24DC-SP 1017064 PHOENIX CONTACT

Coupling relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-PC52-1NO-1NC-24DC-SP



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-PC52-1NO-1NC-24DC-SP
Catalog number	1017064
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-CDE4589EB8
Generated	2026-07-31

Product Overview

Coupling relay

Coupling relay for galvanic separation and power matching for SIL 3 F&G applications, low demand, load diagnostics in the Off and On state over open circuit and short circuit, 1 trip circuit, test pulse filter, plug-in push-in terminal, width 17.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 1017064

Packing unit 1 pc

GTIN 4055626674032

Weight per Piece (excluding packing) 147.160 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 17.5 mm

Height 117.4 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C (observe derating)

Ambient temperature (storage/transport) -40 °C ... 65 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Air pressure (operation) 79 kPa ... 106 kPa

Air pressure (storage/transport) 79 kPa ... 106 kPa

Maximum altitude ≤ 2000 m (Above sea level)

Power supply

Rated control circuit supply voltage US 24 V DC -15 % / +10 %

20.4 V DC ... 26.4 V DC

Rated control supply current IS typ. 75 mA

Power consumption at US typ. 2 W (at US/UD; On state)

Inrush current max. 100 mA

Filter time 2 ms (at A1-A2 in the event of voltage dips at Us)

max. 2 ms (at A1-A2; low test pulse width)

≥ 100 ms (at A1-A2; low test pulse rate)

max. 17 ms (at A1-A2; high test pulse width)

≥ 800 ms (at A1-A2; high test pulse rate)

Diagnostic supply voltage UD 24 V DC -20 % / +25 %

Input current at UD 35 mA (at UD= 24 V)

45 mA (at UD= 19 V)

25 mA (at UD= 30 V)

Inrush current at UD 1.5 A (?t

Power consumption at UD typ. 0.9 W (at UD; Off state)

Prot...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-PC52-1NO-1NC-24DC-SP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.