

INDUSTRIAL COMPONENT DATA

PSR-PLC21-2CO-24DC-PT 1480212 PHOENIX CONTACT Safe coupling relay with forced guide contacts, with galvanic ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-PLC21-2CO-24DC-PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-PLC21-2CO-24DC-PT
Catalog number	1480212
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-67438A7406
Generated	2026-08-01

Product Overview

Safe coupling relay with forced guide contacts, with galvanic separation, 2 switches, 1 channel, push-in connection, width: 14 mm

Coupling Relays

Safe coupling relay with force-guided contacts, electrically isolated, 2 changeover contacts, 1-channel, push-in connection, width: 14 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Technical dataProduct propertiesProduct type Coupling relay

Product family PLC-INTERFACE

Application Forcibly guided contacts

Mechanical service life approx. 107cycles

Relay type Electromechanical relay in accordance with IEC/EN 61810

Insulation characteristics: Air clearances and creepage distances between the power circuits

Overvoltage category III

Pollution degree 2

Times

Typ. starting time with $U_s < 70$ ms (when controlled via A1)

Typical release time < 50 ms (on demand via A1)

Recovery time 500 ms (following demand of the safety function)

Electrical properties Maximum power dissipation for nominal condition 4.825 W (UB= 30 V, US= 24 V, IS= 30 mA, $IL^2 = 37$ A, Rcontact= 0.1 ?)

Nominal operating mode 100% operating factor

Air clearances and creepage distances between the power circuits

Rated insulation voltage 250 V AC

Rated surge voltage/insulation Basic insulation 4 kV between all current paths and housing

Safe isolation, reinforced insulation 6 kV between 250 V load current paths and 24 V logic paths

Supply

Designation A1/A2

Rated control circuit supply voltage US 21.6 V DC ... 28.8 V DC

Rated control circuit supply voltage US 24 V DC -10 % / +20 %

Rated control supply current IS 30 mA

Inrush current typ. 100 mA ($\tau = 10$ ms at Us)

Filter time 1 ms (Test pulse width, high test pulse and low test pulse)

1 s (Test pulse rate, high test pulse and low test pulse)

Power consumption at UD 650 mW (to US)

Protective circuit Serial protection against polarity reversal; Suppressor d...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-PLC21-2CO-24DC-PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.