

INDUSTRIAL COMPONENT DATA

PST 1,0/ 2-3,5 PIN20 R24 1138404 PHOENIX CONTACT Male connector, nominal section: 0.5 mm², color: green, nom..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PST 1,0/ 2-3,5 PIN20 R24



Manufacturer	PHOENIX CONTACT
MPN / Reference	PST 1,0/ 2-3,5 PIN20 R24
Catalog number	1138404
Category	Printed circuit board connector
Minimum order	330 Pcs
Document ID	EO-7D07D9BD49
Generated	2026-08-06

Product Overview

Male connector, nominal section: 0.5 mm², color: green, nominal current: 8 A (Depending on the connector used), nominal voltage (III/2): 250 V, contact surface: Sn, contact connection type: Male, number of rows: 1, number of poles: 2, article family: PST 1.0/.. -V, pitch: 3.5 mm, mounting: THR welding/wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, plug-in system: COMBICON PST 1.0, lock: without, fixing type: without, packaging type: 24 mm wide strap

Male connector, nominal section: 0.5 mm², colour: green, rated current: 8 A (Depending on the connector used), sizing voltage (III/2): 250 V, surface contacts: Tin, contact type: Male, Number of rows: 1, Number of poles per row: 2, article family: PST 1,0/.. -V, pitch: 3.5 mm, mounting: WELDING THR, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, Stecksystem: COMBICON COMPACT PST 1, Locking: sin, packing type: 24 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1138404 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Rated current I_n (EF008250)

8 A

Rated voltage (EF000228)

250 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.2 mm

Length pin (EF006825)

2 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of fastening (EF002442)

Other

Type of banding (EF007011)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PST 1,0/ 2-3,5 PIN20 R24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.