

INDUSTRIAL COMPONENT DATA

PST 1,3/ 3-5,0 GY VPE250 1107420 PHOENIX CONTACT Male connector, nominal current: 12 A, number of poles: 3, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PST 1,3/ 3-5,0 GY VPE250



Manufacturer	PHOENIX CONTACT
MPN / Reference	PST 1,3/ 3-5,0 GY VPE250
Catalog number	1107420
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-311A7D3E46
Generated	2026-08-06

Product Overview

PST 1,3/ 3-5,0 GY VPE250 1107420 PHOENIX CONTACT Male connector, nominal current: 12 A, number of poles: 3, ..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	Fixed connector
Contact type (EF001587)	Pin
Number of plug-in contact rows (EF006935)	1
Modular spacing contacts (EF007326)	5 mm
Modular spacing connections (EF006827)	5 mm
Rated current In (EF008250)	12 A
Rated voltage (EF000228)	320 V
Rated surge voltage (EF002993)	4 kV
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Material of contact surface (EF004020)	Tin
Type of electric connection (EF003961)	Other
Diameter connection pin (EF006823)	1.3 mm
Length pin (EF006825)	3.5 mm
Material insulation body (EF007543)	Other

CONTINUED**Technical Specifications**

TECHNICAL ATTRIBUTE	VALUE
Housing colour (EF000136)	Grey
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-40 °C
Type of fastening (EF002442)	Other
Type of banding (EF007011)	Carton (for SMD)

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Male connector, nominal current: 12 A, number of poles: 3, pitch: 5 mm, color: gray, surface contacts: Tin, assembly: Soldering THR

Male connector, nominal section: 1.5 mm², color: gray, nominal current: 12 A (Depending on the connector used), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 3, family of articles: PST 1.3/. -V, pitch: 5 mm, mounting: THR solder, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PST 1,3/ 3-5,0 GY VPE250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.