

INDUSTRIAL COMPONENT DATA

PST 1,3/ 3-5,0 GY VPE250 1107420 PHOENIX CONTACT Male connector, nominal current: 12 A, number of poles: 3, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PST 1,3/ 3-5,0 GY VPE250



Manufacturer	PHOENIX CONTACT
MPN / Reference	PST 1,3/ 3-5,0 GY VPE250
Catalog number	1107420
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-311A7D3E46
Generated	2026-08-06

Product Overview

PST 1,3/ 3-5,0 GY VPE250 1107420 PHOENIX CONTACT Male connector, nominal current: 12 A, number of poles: 3, ..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	Fixed connector
Contact type (EF001587)	Pin
Number of plug-in contact rows (EF006935)	1
Modular spacing contacts (EF007326)	5 mm
Modular spacing connections (EF006827)	5 mm
Rated current In (EF008250)	12 A
Rated voltage (EF000228)	320 V
Rated surge voltage (EF002993)	4 kV
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Material of contact surface (EF004020)	Tin
Type of electric connection (EF003961)	Other
Diameter connection pin (EF006823)	1.3 mm
Length pin (EF006825)	3.5 mm
Material insulation body (EF007543)	Other

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Housing colour (EF000136)	Grey
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-40 °C
Type of fastening (EF002442)	Other
Type of banding (EF007011)	Carton (for SMD)

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Male connector, nominal current: 12 A, number of poles: 3, pitch: 5 mm, color: gray, surface contacts: Tin, assembly: Soldering THR

Male connector, nominal section: 1.5 mm², color: gray, nominal current: 12 A (Depending on the connector used), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 3, family of articles: PST 1.3/. -V, pitch: 5 mm, mounting: THR solder, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PST 1,3/ 3-5,0 GY VPE250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.