

INDUSTRIAL COMPONENT DATA

PST 1,3/ 5-5,0 L22,5 1172269 PHOENIX CONTACT Blade, nominal section: 1.5 mm², color: black, nominal current:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PST 1,3/ 5-5,0 L22,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	PST 1,3/ 5-5,0 L22,5
Catalog number	1172269
Category	Printed circuit board connector
Minimum order	200 Pcs
Document ID	EO-A5978F4CCE
Generated	2026-08-06

Product Overview

Blade, nominal section: 1.5 mm², color: black, nominal current: 12 A (Depending on the connector used), nominal voltage (III/2): 320 V, contact surface: Sn, type of contact connection: Male, number of rows: 1, number of poles: 5, family of articles: PST 1.3/.. -V, pitch: 5 mm, mounting: THR welding/wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, plug-in system: COMBICON PST 1.3, locking: without, clamping type: without, packaging type: boxed Male connector, nominal section: 1.5 mm², colour: black, rated current: 12 A (Depending on the connector used), sizing voltage (III/2): 320 V, surface contacts: Tin, contact type: Male, Number of rows: 1, Number of poles per row: 5, item family: PST 1.3/.. -V, pitch: 5 mm, mounting: Welding THR, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, Stecksystem: COMBICON COMPACT PST 1.3, Locking: sin, packing type: packaging fits

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1172269 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

1
Modular spacing contacts (EF007326)
5 mm
Modular spacing connections (EF006827)
5 mm
Rated current I_n (EF008250)
12 A
Rated voltage (EF000228)
320 V
Rated surge voltage (EF002993)
4 kV
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2
Material of contact surface (EF004020)
Tin
Type of electric connection (EF003961)
Other
Diameter connection pin (EF006823)
1.3 mm
Length pin (EF006825)
3.5 mm
Material insulation body (EF007543)
Other
Housing colour (EF000136)
Black
Inflammability class of insulation material according to UL94 (EF002521)
V0
Operating temperature (EF002393)
-40 °C
Type of fastening (EF002442)
Other
Type of banding (EF007011)
Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PST 1,3/ 5-5,0 L22,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.