

INDUSTRIAL COMPONENT DATA

PST 1,3/ 7-5,0 L18 1795006 PHOENIX CONTACT Male connector, nominal current: 12 A, number of poles: 7, pitch:...

Brand: PHOENIX CONTACT | Manufacturer Part Number: PST 1,3/ 7-5,0 L18



Manufacturer	PHOENIX CONTACT
MPN / Reference	PST 1,3/ 7-5,0 L18
Catalog number	1795006
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-673EE749DD
Generated	2026-08-06

Product Overview

Male connector, nominal current: 12 A, number of poles: 7, pitch: 5 mm, color: black, surface of contact: Tin, assembly: Soldering THR, The maximum current depends on the connector used. Of the two current values, it is determining the lowest value for the connector and the male connector. The male connector is manufactured in plastic resistant to high temperatures, which is suitable for the process of reflow soldering.

Male connector, nominal section: 1.5 mm², color: black, nominal current: 12 A (Depending on the connector used), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: PST 1.3/. -V, pitch: 5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, plug-in system: COMBICON PST 1.3, locking: without, fixing type: without, packaging type: boxed, The maximum current depends on the connector used. Of the two current values, the lower value for the connector and the male connector is decisive. The plug is made of high-temperature resistant plastic, making it suitable for the reflow soldering process.

Plug, nominal cross-section: 1.5 mm², colour: black, rated current: 12 A (regardless of the connector used), dimensioning voltage (III/2): 320 V, contact surface: Sn, contact connection type: plug, number of p...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Male connector, nominal current: 12 A, voltage and sizing (III/2): 320 V, number of poles: 7, pitch: 5 mm, color: black, surface of contact: Tin, assembly: Soldering THR, The maximum current depends on the connector used. Of the two current values, it is determining the lowest value for the connector and the male connector. The male connector is manufactured in

plastic resistant to high temperatures, which is suitable for the process of reflow soldering.

Data commercial

Key order One million seven hundred ninety five thousand six

Packing unit 50 pcs

Key selling AACLBA -

Minimum order quantity 50 pcs

EAN Four trillion forty six billion three hundred fifty six million six hundred twenty five thousand two hundred forty one

Unit weight (excluding packaging) 1,637 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin DE (Germany)

Dimensions

Length [l] 2.8 mm

Width 35 mm

Step 5 mm

Average 30 mm

Width [w] 35 mm

Height [h] 18 mm

Height of construction 14,5 mm

Length of the pin welding 3.5 mm

Dimensions of pin $\varnothing$ 1.3 mm

Length 2.8 mm

Overview

Family of articles PST 1,3/..-V

Tension and sizing (III/3) 250 V

Connection according to standard EN-VDE

Nominal current IN 12 To

Class of flammability according to UL 94 V0

Color black

Number of poles Seven

Standards and specifications

Connection according to standard EN-VDE

Class of flammability according to UL 94 V0

Environmental Product Compliance

China RoHS Space of time for t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PST 1,3/ 7-5,0 L18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.