

INDUSTRIAL COMPONENT DATA

PSTD 0,65X0,65/9-3IS-2,54 1252178 PHOENIX CONTACT Male connector, color: black, rated current: 3 A (per cont..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSTD 0,65X0,65/9-3IS-2,54



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSTD 0,65X0,65/9-3IS-2,54
Catalog number	1252178
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-439D3E27DD
Generated	2026-08-04

Product Overview

Male connector, color: black, rated current: 3 A (per contact), rated voltage (III/2): 100 V, contact connection type: Male, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, pitch: 2.54 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.5 mm, Lock: Without, Packaging Type: Boxed Packaging

Male connector, color: black, rated current: 3 A (per contact), sizing voltage (III/2): 100 V, contact type: Male, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, step: 2.54 mm, mounting: THR welding, pin arrangement: linear pin arrangement, pin length [P]: 2.5 mm, Locking: without, type of packaging: packaged in box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

ETIM for 1252178 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

9

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

2.54 mm

Modular spacing connections (EF006827)

2.54 mm

Rated current I_n (EF008250)

3 A

Rated voltage (EF000228)

100 V

Rated surge voltage (EF002993)

1.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Type of electric connection (EF003961)

Other

Length pin (EF006825)

2.5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Black

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSTD 0,65X0,65/9-3IS-2,54 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.