

INDUSTRIAL COMPONENT DATA

PT 10-FSI/C-LED 24 1088500 PHOENIX CONTACT Rail terminal for fuse, fuse type: Flat, fuse type: C, nominal vo..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 10-FSI/C-LED 24



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 10-FSI/C-LED 24
Catalog number	1088500
Category	Fuse terminal block
Minimum order	25 Pcs
Document ID	EO-00C76B8B19
Generated	2026-08-03

Product Overview

Rail terminal for fuse, fuse type: Flat, fuse type: C, nominal voltage: 24 V, nominal current: 25 A, connection type: Push-in connection, Dimensioning cross-section: 10 mm², cross-section: 0.5 mm²- 16 mm², mounting class: NS 35/7.5, NS 35/15, colour: black

Fuse rail terminal, fuse type: Flat, connection type: Push-in connection, section: 0.5 mm²- 16 mm², AWG: 20 - 6, rated current: 30 A, rated voltage: 400 V, width: 10.2 mm, fuse type: C, mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1088500 Terminal blocks (EC000899)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.5 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.5 mm²

Connectable conductor cross section solid-core (EF007337)

0.5 mm²

Rated current I_n (EF008250)

25 A

Rated voltage (EF000228)

24 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of levels (EF002659)

1

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

10.15 mm

Height (EF000040)

88.9 mm

Depth (EF000049)

50.95 mm

Closing plate required (EF002525)

No

Colour (EF000007)

Black

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 10-FSI/C-LED 24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.