

## INDUSTRIAL COMPONENT DATA

# PT 1,5/ 2-PVH-5,0-A 1935019 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 2-PVH-5,0-A



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | PT 1,5/ 2-PVH-5,0-A |
| Catalog number  | 1935019             |
| Category        | Cable connector     |
| Minimum order   | 250 Pcs             |
| Document ID     | EO-4A243865EC       |
| Generated       | 2026-08-05          |

## Product Overview

PCB terminal block

Connector for printed circuit board, nominal section: 1.5 mm<sup>2</sup>, color: green, nominal current: 12 A, nominal voltage (III/2): 400 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: PT 1.5/.. -PVH-A, pitch: 5 mm, connection type: Screw connection with wire protection bracket, screw clamping form: H1L Philipps-Recess with longitudinal groove, conductor/printed circuit board connection direction: 0 °, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

Key Commercial Data

Orderkey 1935019

Packing unit 250 pc

Minimum order quantity 250 pc

GTIN 4017918916787

Weight per Piece (excluding packing) 2.270 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [ l ] 19.7 mm

Width [ w ] 10 mm

Height [ h ] 11.4 mm

Pitch 5 mm

Dimension a 5 mm

General

Range of articles PT 1,5/-PVH-A

Number of positions 2

Connection method Screw connection with wire protector

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 1.5 mm<sup>2</sup>

Maximum load current 10 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 5 mm

Screw thread M2,6

Tightening torque, min 0.4 Nm

Tightening torque max 0.4 Nm

Connection data

Conductor cross section solid min. 0.2 mm<sup>2</sup>

Conductor cross section solid max. 2.5 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm<sup>2</sup>

Conductor cross section A...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 2-PVH-5,0-A with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.