


INDUSTRIAL COMPONENT DATA

PT 1,5/ 4-PVH-3,5-A 1984183 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 4-PVH-3,5-A



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/ 4-PVH-3,5-A
Catalog number	1984183
Category	Cable connector
Minimum order	250 Pcs
Document ID	EO-A1101A07C4
Generated	2026-08-03

Product Overview

PCB terminal block

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 6 A, nominal voltage (III/2): 200 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: PT 1.5/..-PVH-A, pitch: 3.5 mm, connection type: Screw connection with wire protection bracket, screw clamping method: HOL Philipps-Recess with longitudinal groove, driver/printed circuit board connection direction: 0 °, plug-in system: COMBICON PST 1.0, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1984183

Packing unit 250 pc

Minimum order quantity 250 pc

Note Made to Order (non-returnable)

GTIN 4046356036016

Weight per Piece (excluding packing) 2.700 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Length [l] 11 mm

Width [w] 14 mm

Height [h] 11 mm

Pitch 3.5 mm

Dimension a 10.5 mm

General

Range of articles PT 1,5/..-PVH-A

Number of positions 4

Connection method Screw connection with wire protector

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 200 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Nominal cross section 1.5 mm²

Maximum load current 6 A

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 5 mm

Screw thread M2

Tightening torque, min 0.25 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 0.34 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 0.5 mm²

Minimum AWG according to UL/CUL 26

M...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 4-PVH-3,5-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.