

INDUSTRIAL COMPONENT DATA

PT 1,5/ 4-PVH-5,0 BDNZ:+,+,-,- 1724174 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 4-PVH-5,0 BDNZ:+,+,-,-



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/ 4-PVH-5,0 BDNZ:+,+,-,-
Catalog number	1724174
Category	Cable connector
Minimum order	250 Pcs
Document ID	EO-BF69829104
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 400 V, contact surface: Tin, contact type: Female connection, Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, number of connections: 4, family of articles: PT 1.5/.. -PVH, pitch: 5 mm, connection type: Screw connection with wire protection bracket, conductor connection direction/printed circuit board: 0 °, Stecksyst.: COMBICON COMPACT PST 1.3, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1724174

Packing unit 250 pc

Minimum order quantity 250 pc

Note Made to Order (non-returnable)

GTIN 4046356123891

Weight per Piece (excluding packing) 4.570 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 11.4 mm

Width [w] 20 mm

Height [h] 11.4 mm

Pitch 5 mm

Dimension a 15 mm

General

Range of articles PT 1,5/..-PVH

Number of positions 4

Connection method Screw connection with wire protector

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 0.75 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 4-PVH-5,0 BDNZ:+,+,-,- with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.