

## INDUSTRIAL COMPONENT DATA

# PT 1,5/ 8-5,0-H KMGY 1730210 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 8-5,0-H KMGY



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | PT 1,5/ 8-5,0-H KMGY           |
| Catalog number  | 1730210                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 100 Pcs                        |
| Document ID     | EO-FC3EED79B0                  |
| Generated       | 2026-08-06                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm<sup>2</sup>, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, article family: PT 1.5/.. -H, pitch:5 mm, connection type: Screw connection with wire protection bracket, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: light gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

Key Commercial Data

Orderkey 1730210

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356152082

Weight per Piece (excluding packing) 7.730 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [ l ] 9 mm

Pitch 5 mm

Dimension a 35 mm

Height 11.4 mm

Height [ h ] 11.3 mm

Solder pin [P] 3.5 mm

Pin spacing 5 mm

Hole diameter 1.3 mm

General

Range of articles PT 1,5/..-H

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 17.5 A

Nominal cross section 1.5 mm<sup>2</sup>

Maximum load current 17.5 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 5 mm

Number of positions 8

Screw thread M2,6

Tightening torque, min 0.35 Nm

Tightening torque max 0.4 Nm

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

2 conductors with same cross section, solid min. 0.2 mm<sup>2</sup>

2 conductors with same cross section, solid max. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded min. 0.2 mm<sup>2</sup>

2 conductors with same cross section, stranded max. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 8-5,0-H KMGY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.