

## INDUSTRIAL COMPONENT DATA

# PT 1,5/S-QUATTRO-MT BK 1548369 PHOENIX CONTACT

## Blade interruptible terminal block, nominal voltage: 400 V, n..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/S-QUATTRO-MT BK



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | PT 1,5/S-QUATTRO-MT BK            |
| Catalog number  | 1548369                           |
| Category        | (Knife) disconnect terminal block |
| Minimum order   | 50 Pcs                            |
| Document ID     | EO-64854141CF                     |
| Generated       | 2026-08-05                        |

### Product Overview

Blade interruptible terminal block, nominal voltage: 400 V, nominal current: 10 A, 1st floor, connection type: Push-in connection, Dimensioning cross-section: 1.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, mounting: NS 35/7.5, NS 35/15, colour: black

Knife-disconnect terminal block, nom. voltage: 400 V, nominal current: 10 A, 1 level, connection method: Push-in connection, Rated cross section: 1.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, mounting: NS 35/7.5, NS 35/15, color: black

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Modular TBs

### Additional Product Information

Technical dataProduct propertiesProduct type Disconnect terminal block

Number of connections 4

Number of rows 1

Potentials 1

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesMaximum power dissipation for nominal condition 0.56 W

Connection dataNumber of connections per level 4

Nominal cross section 1.5 mm<sup>2</sup>

1 level

Stripping length 8 mm ... 10 mm  
Internal cylindrical gage A1 / B1  
Connection in acc. with standard IEC 60947-7-1  
Conductor cross section rigid 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Cross section AWG 26 ... 14 (converted acc. to IEC)  
Conductor cross section flexible 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section, flexible [AWG] 26 ... 14 (converted acc. to IEC)  
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm<sup>2</sup> ... 1 mm<sup>2</sup> Using the AI-S 1-8 TQ ferrule, Item No. 1200293, is recommended  
Nominal current 10 A  
Maximum load current 10 A  
Nominal voltage 400 V  
Nominal cross section 1.5 mm<sup>2</sup>  
1 level Connection cross sections directly pluggable  
Conductor cross section rigid 0.25 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Flexible conductor cross section (ferrule with plastic sleeve) 0.34 mm<sup>2</sup> ... 1 mm<sup>2</sup>  
Dimensions Width 3.5 mm  
End cover width 0.8 mm  
Height 76.9 mm  
Depth 30.5 mm  
Depth on NS 35/7,5 32 mm  
Depth on NS 35/15 39.5 mm  
Material specifications Color black  
Flammability rating accordi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/S-QUATTRO-MT BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.