

INDUSTRIAL COMPONENT DATA

PT 1,5/S-TWIN OG 3208157 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/S-TWIN OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/S-TWIN OG
Catalog number	3208157
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-CCDD5B17B
Generated	2026-08-03

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 500 V, nominal current: 17.5 A, number of connections: 3, connection type: Push-in connection, 1st floor, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3208157

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626327136

Weight per Piece (excluding packing) 4.470 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 3

Potentials 1Nominal cross section 1.5 mm²

Color orange

Insulating material PA

Flammability rating according to UL 94 V0

Area of application Machine building

Plant engineering

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.56 W

Maximum load current 17.5 A

Nominal current I_N 17.5 ANominal voltage U_N 500 V

Open side panel Yes

Dimensions

Width 3.5 mm

End cover width 2.2 mm

Length 54 mm

Height 30.5 mm

Height NS 35/7,5 32 mm

Height NS 35/15 39.5 mm

Connection data

Connection method Push-in connection

Connection in acc. with standard IEC 60947-7-1

Conductor cross section solid min. 0.14 mm²Conductor cross section solid max. 1.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

Conductor cross section flexible min. 0.14 mm²Conductor cross section flexible max. 1.5 mm²

Min. AWG conductor cross section, flexible 26

Max. AWG conductor cross section, flexible 14

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/S-TWIN OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.