

INDUSTRIAL COMPONENT DATA

PT 2,5/15-7,5-V 1988082 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5/15-7,5-V



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5/15-7,5-V
Catalog number	1988082
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-4477AA6370
Generated	2026-08-04

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 32 A, nominal voltage (III/2): 800 V, nominal section: 2.5 mm², number of potentials: 15, number of rows: 1, number of poles per row: 15, article family: PT 2.5/.. -V, pitch: 7.5 mm, connection type: Screw connection with wire protection bracket, mounting: Wave soldering, conductor/printed circuit board connection direction: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.1 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1988082

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4046356036610

Weight per Piece (excluding packing) 20.350 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [L] 13.5 mm

Pitch 7.5 mm

Dimension a 105 mm

Width [w] 112.5 mm

Height 9 mm

Height [h] 13.1 mm

Solder pin [P] 4.1 mm

Pin spacing 7.5 mm

Hole diameter 1.3 mm

General

Range of articles PT 2,5/..-V

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 800 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 32 A

Nominal cross section 2.5 mm²

Maximum load current 32 A (current values dependent on no. of pos., dimensioning of printed circuits, and ambient temperature)

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 6.5 mm

Number of positions 15

Screw thread M3

Tightening torque, min 0.45 Nm

Tightening torque max 0.5 Nm

Connection data

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5/15-7,5-V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.