

INDUSTRIAL COMPONENT DATA

PT 2,5/ 2-5,0-H BK PA2 1706776 PHOENIX CONTACT Terminal block for printed circuit board, rated current: 32 A..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5/ 2-5,0-H BK PA2



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5/ 2-5,0-H BK PA2
Catalog number	1706776
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-9C0ECB6D57
Generated	2026-08-05

Product Overview

Terminal block for printed circuit board, rated current: 32 A, rated voltage: 400 V, pitch: 5 mm, number of poles: 2, connection type: Screw connection with wire protection bracket, mounting: Wave soldering, connection direction conductor/printed circuit board: 0 °, color: black

Terminal block for printed circuit board, nominal current: 32 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: PT 2.5/.. -H, pitch: 5 mm, connection type: Screw connection with wire protection bracket, screw clamping form: H1L Philipps-Recess with longitudinal groove, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.1 mm, number of solder pins per potential: 1, Packing Type: Boxed Packed Printed circuit board terminal, nominal current: 32 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², number of potentials: 2, number of rows: 1, number of positions per row: 2, product range: PT 2,5/..-H, pitch: 5 mm, connection method: Screw connection with wire protector, screw head form: H1L Slotted Phillips recess, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: black, Pin layout: Linear pinning, Solder pin [P]: 4.1 mm, number of solder pins per potential: 1, type....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family PT 2,5/..-H

Product line COMBICON Terminals M

Type PC termination block

Number of positions 2

Pitch 5 mm

Number of connections 2

Number of rows 1

Number of potentials 2

Pin layout Linear pinning

Solder pins per potential 1

Data management status

Article revision 02

Electrical propertiesNominal current IN 32 A

Nominal voltage UN 400 V

Rated voltage (III/3) 250 V

Rated surge voltage (III/3) 4 kV

Rated voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Rated voltage (II/2) 630 V

Rated surge voltage (II/2) 4 kV

Connection dataConnection technology

Type PC termination block

Nominal cross section 2.5 mm²

Conductor connection

Connection method Screw connection with wire protector

Conductor cross section rigid 0.5 mm² ... 4 mm²

Conductor cross section flexible 0.5 mm² ... 4 mm²

Conductor cross section AWG 20 ... 10

Conductor cross section flexible, with ferrule without plastic sleeve 0.5 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.5 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.5 mm² ... 1.5 mm²

2 conductors with same cross section, flexible 0.5 mm² ... 1.5 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.5 mm² ... 0.75 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1.5 mm²

Stripping length 6.5 mm

Drive form screw head Slotted Philli...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5/ 2-5,0-H BK PA2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.