

INDUSTRIAL COMPONENT DATA

PT 2,5/ 2-5,0-V-S 1705753 PHOENIX CONTACT Screw compact terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5/ 2-5,0-V-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5/ 2-5,0-V-S
Catalog number	1705753
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-A42ABFB6A4
Generated	2026-08-04

Product Overview

Screw compact terminal block

Terminal block for printed circuit board, nominal current: 32 A, dimensioning voltage (III/2): 400 V, nominal section: 2.5 mm², Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, family of articles: PT 2.5/.. -V, pitch: 5mm, connection type: Screw connection with wire protection bracket, mounting: Wave soldering, conductor/printed circuit board connection direction: 90°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.1 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1705753

Packing unit 250 pc

Minimum order quantity 250 pc

Note Made to Order (non-returnable)

GTIN 4046356032520

Weight per Piece (excluding packing) 2.440 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 13.5 mm

Pitch 5 mm

Dimension a 5 mm

Height 14 mm

Height [h] 9 mm

Solder pin [P] 4.1 mm

Pin spacing 5 mm

Hole diameter 1.3 mm

General

Range of articles PT 2,5/..-V

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 32 A

Nominal cross section 2.5 mm²

Maximum load current 32 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 6.5 mm

Number of positions 2

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.5 Nm

Connection data

Conductor cross section solid min. 0.75 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section flexible min. 0.75 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.75 mm²

Conductor cross section flexible, with ferrule with plastic sl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5/ 2-5,0-V-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.