

INDUSTRIAL COMPONENT DATA

PT 2,5-4PV BU 1336409 PHOENIX CONTACT Multi-floor terminal block, with potential splicers, nominal voltage: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-4PV BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-4PV BU
Catalog number	1336409
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-EA3ABC3A50
Generated	2026-08-05

Product Overview

Multi-floor terminal block, with potential splicers, nominal voltage: 500 V, nominal current: 18 A, number of connections: 8, number of poles: 3, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: blue

Multi-level terminal block, with equipotential bonder, nom. voltage: 500 V, nominal current: 18 A, number of connections: 8, number of positions: 3, connection method: Push-in connection, Rated cross section: 2.5 mm², cross section: 0.14 mm² - 4 mm², mounting type: NS 35/7,5, NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Multi-level terminal block

Number of positions 3

Number of connections 8

Number of rows 4

Potentials 1

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesMaximum power dissipation for nominal condition 0.77 W

Connection dataNumber of connections per level 2

Nominal cross section 2.5 mm²
Cross section AWG (converted acc. to IEC)
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A3
B3
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.14 mm² ... 4 mm²
Cross section AWG 26 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
Nominal current 18 A
Maximum load current 20 A (with 4 mm² conductor cross-section)
Nominal voltage 500 V
Nominal cross section 2.5 mm²
Connection cross sections directly pluggable
Conductor cross section rigid 0.34 mm² ... 4 mm²
Conductor cross section, rigid [AWG] 20 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.5 mm² ... 2.5 mm²
Conductor cross-section flexible (ferrule without plastic sleeve) 0.5 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.5 mm² ... 2.5 mm²
Dimensions Width 5.2 mm
End cover width 2.2 mm
He...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-4PV BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.