


INDUSTRIAL COMPONENT DATA

PT 2,5-L/L/N 3210500 PHOENIX CONTACT Multi-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-L/L/N



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-L/L/N
Catalog number	3210500
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-3021A48309
Generated	2026-08-04

Product Overview

Multi-level terminal block

Multi-floor terminal block, nominal voltage: 500 V, nominal current: 20 A, connection type: Push-in connection, 1., 2. and 3rd floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

Multi-level terminal block, nom. voltage: 500 V, nominal current: 20 A, connection method: Push-in connection, 1st, 2nd and 3rd level, Rated cross section: 2.5 mm², cross section: 0.14 mm² - 4 mm², mounting type: NS 35/7,5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Technical dataProduct propertiesProduct type Multi-level terminal block

Number of connections 6

Number of rows 3

Potentials 3

Data management status

Article revision 14

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 6 kV

Maximum power dissipation for nominal condition 0.77 W

Connection data Number of connections per level 2

Nominal cross section 2.5 mm²

1st, 2nd and 3rd level

Stripping length 8 mm ... 10 mm

Internal cylindrical gage A3

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.14 mm² ... 4 mm²

Cross section AWG 26 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.14 mm² ... 4 mm²

Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm²

Nominal current 20 A

Maximum load current 24 A (with 4 mm² conductor cross section, rigid)

Nominal voltage 500 V

Nominal cross section 2.5 mm²

1st, 2nd and 3rd level Connection cross sections directly pluggable

Conductor cross section rigid 0.34 mm² ... 4 mm²

Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm² ... 2.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.34 mm² ... 2.5 mm²

Ex data Rated data....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-L/L/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.