

## INDUSTRIAL COMPONENT DATA

# PT 2,5-MTB GN 1107089 PHOENIX CONTACT Terminal interruptible blade, rated voltage: 400 V, nominal current: 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-MTB GN



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | PT 2,5-MTB GN                     |
| Catalog number  | 1107089                           |
| Category        | (Knife) disconnect terminal block |
| Minimum order   | 50 Pcs                            |
| Document ID     | EO-7692D460C1                     |
| Generated       | 2026-08-02                        |

## Product Overview

Terminal interruptible blade, rated voltage: 400 V, nominal current: 16 A, connection type: Connection push-in connection, section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, length: 70,1 mm, width: 5,2 mm, color: green, assembly: NS 35/7,5, NS 35/15  
Blade interruptible terminal block, nominal voltage: 400 V, nominal current: 16 A, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting: NS 35/7.5, NS 35/15, colour: green

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

ETIM for 1107089 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm<sup>2</sup>

Connectable conductor cross section solid-core (EF007337)

0.14 mm<sup>2</sup>

Rated current I<sub>n</sub> (EF008250)

16 A

Rated voltage (EF000228)

400 V  
Type of electrical connection 1 (EF002526)  
Other  
Type of electrical connection 2 (EF002527)  
Other  
Number of clamp positions per level (EF002660)  
2  
Internally connected stages (EF002661)  
Yes  
Mounting method (EF000003)  
DIN rail (top hat rail) 35 mm  
Material insulation body (EF007543)  
Other  
Inflammability class of insulation material according to UL94 (EF002521)  
V0  
Width (EF000008)  
5.2 mm  
Height (EF000040)  
70.1 mm  
Depth (EF000049)  
35.2 mm  
Closing plate required (EF002525)  
Yes  
Colour (EF000007)  
Green  
Type of cross disconnection (EF002546)  
None  
With integrated test socket (EF002547)  
No

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-MTB GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.