

INDUSTRIAL COMPONENT DATA

PT 2,5-PE/L/L/L 1336407 PHOENIX CONTACT Ground terminal, number of connections: 8, number of poles: 4, conne..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-PE/L/L/L



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-PE/L/L/L
Catalog number	1336407
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-26FD6B9923
Generated	2026-08-06

Product Overview

Ground terminal, number of connections: 8, number of poles: 4, connection type: Push-in connection, Ground conductor connection, Dimensioning section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², connection type: Push-in connection, Pitch floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, Color: Gray

Protective conductor terminal, number of connections: 8, number of positions: 4, connection method: Push-in connection, Protective conductor connection, Rated cross section: 2.5 mm², cross section: 0.14 mm² - 4 mm², connection method: Push-in connection, Feed-through level, Rated cross section: 2.5 mm², cross section: 0.14 mm² - 4 mm², mounting type: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Technical dataNotesGeneral

Note When establishing a connection on the open housing side of a feed-through modular terminal block of the same series and size, the block must be provided with a cover if the expected insulation voltage is >690 V.

The max. load current must not be exceeded by the total current of all connected conductors.

Product propertiesProduct type Ground terminal block

Number of positions 4

Number of connections 8
Number of rows 4
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical properties Rated surge voltage 6 kV
Connection data Number of connections per level 2
Nominal cross section 2.5 mm²
Cross section AWG (converted acc. to IEC)
Protective conductor connection
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A3
B3
Connection in acc. with standard IEC 60947-7-2
Conductor cross section rigid 0.14 mm² ... 4 mm²
Cross section AWG 26 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
Nominal cross section 2.5 mm²
Feed-through level
Stripping length 8 mm ... 10 mm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.14 mm² ... 4 mm²
Cross section AWG 26 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-PE/L/L/L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.