

INDUSTRIAL COMPONENT DATA

PT 2,5-QUATTRO-MTB TMR 1081461 PHOENIX CONTACT

Terminal interruptible blade, with blade seccionadora rotated..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-QUATTRO-MTB TMR



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-QUATTRO-MTB TMR
Catalog number	1081461
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-F9E2A8C968
Generated	2026-08-05

Product Overview

Terminal interruptible blade, with blade seccionadora rotated 180°, rated voltage: 400 V, nominal current: 16 A, Connection type: Connection push-in connection, section: 0.14 mm²-4 mm², AWG: 26-12, length: 92,2 mm, width: 5,2 mm, color: gray, mounting: NS 35/7,5, NS 35/15

Blade interruptible terminal block, with 180° rotating disconnect blade, nominal voltage: 400 V, nominal current: 16 A, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

ETIM for 1081461 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Rated current I_n (EF008250)

16 A
Rated voltage (EF000228)
400 V
Type of electrical connection 1 (EF002526)
Other
Type of electrical connection 2 (EF002527)
Other
Number of clamp positions per level (EF002660)
4
Internally connected stages (EF002661)
Yes
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
Material insulation body (EF007543)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Width (EF000008)
5.2 mm
Height (EF000040)
92.2 mm
Depth (EF000049)
35.2 mm
Closing plate required (EF002525)
Yes
Colour (EF000007)
Grey
Type of cross disconnection (EF002546)
None
With integrated test socket (EF002547)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-QUATTRO-MTB TMR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.