

INDUSTRIAL COMPONENT DATA

PT 2,5-TGBD 1107096 PHOENIX CONTACT Borne of the passing lane, The current and voltage are determined by the..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-TGBD



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-TGBD
Catalog number	1107096
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-D68CB29938
Generated	2026-08-06

Product Overview

Borne of the passing lane, The current and voltage are determined by the connector used., nominal voltage: 400 V, nominal current: 16 A, connection type: Connection push-in connection, number of connections: 2, section: 0.14 mm² - 4 mm², AWG: 26 - 12, width: 5,2 mm, height: 35,3 mm, color: grey, type of mounting: NS 35/7,5, NS 35/15

Feed-through rail terminal, Current and voltage are determined by the connector used., nominal voltage: 400 V, nominal current: 16 A, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1107096 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Rated current I_n (EF008250)

16 A
Rated voltage (EF000228)
400 V
Type of electrical connection 1 (EF002526)
Other
Type of electrical connection 2 (EF002527)
Other
Number of clamp positions per level (EF002660)
2
Internally connected stages (EF002661)
Yes
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
Material insulation body (EF007543)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Width (EF000008)
5.2 mm
Height (EF000040)
70.1 mm
Depth (EF000049)
35.3 mm
Closing plate required (EF002525)
Yes
Colour (EF000007)
Grey
Type of cross disconnection (EF002546)
None
With integrated test socket (EF002547)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-TGBD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.