

INDUSTRIAL COMPONENT DATA

PT 4-FSI/F-LED 70 1058965 PHOENIX CONTACT Fuse modular terminal block PT 4-FSI/F-LED 70 1058965

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 4-FSI/F-LED 70



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 4-FSI/F-LED 70
Catalog number	1058965
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-4F3E905CC4
Generated	2026-08-06

Product Overview

Fuse modular terminal block - PT 4-FSI/F-LED 70 - 1058965

Fuse terminal block, fuse type: Flat, fuse type: Model F (miniature), nominal voltage: 70 V, nominal current: 10 A, connection type: Push-in connection, Dimensioning cross-section: 4 mm², cross-section: 0.2 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Fuse modular terminal block, nominal current: 10 A, nom. voltage: 70 V

Key Commercial Data

Orderkey 1058965

Packing unit 1

GTIN 4055626703152

Custom tariff number 85369010

General

Maximum current with single arrangement 15 A

Voltage LED 70 V

Current LED 1.8 mA

Maximum load current 15 A

Nominal current IN 10 A

Nominal voltage UN 70 V

Open side panel Yes

Classifications

eCI@ss

eCI@ss 5.1 27141100

eCI@ss 6.0 27141100

eCI@ss 7.0 27141116

eCI@ss 8.0 27141116

eCI@ss 9.0 27141116

ETIM

ETIM 5.0 EC000899

ETIM 6.0 EC000899

ETIM 7.0 EC000899

ETIM for 1058965 Terminal blocks (EC000899)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Rated current I_n (EF008250)

10 A

Rated voltage (EF000228)

70 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of levels (EF002659)

1

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

6.15 mm

Height (EF000040)

55.9 mm

Depth (EF000049)

35.25 mm

Closing plate required (EF002525)

Yes

Colour (EF000007)

Black

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 4-FSI/F-LED 70 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.