

INDUSTRIAL COMPONENT DATA

PT 4-HESILED 24 (5X20) BU/BU 3211905 PHOENIX CONTACT

Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 4-HESILED 24 (5X20) BU/BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 4-HESILED 24 (5X20) BU/BU
Catalog number	3211905
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-A1DF929E74
Generated	2026-08-05

Product Overview

Fuse modular terminal block

Fuse rail terminal, fuse type: Glass/ceramic/..., connection type: Push-in connection, section: 0.2 mm²- 6 mm², AWG: 24 - 10, rated current: 6.3 A, rated voltage: 24 V, width: 6.2 mm, fuse type: G/5 x 20, mounting class: NS 35/7.5, NS 35/15, colour: blue

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: G / 5 x 20, nom. voltage: 24 V, nominal current: 6.3 A, connection method: Push-in connection, Rated cross section: 1 mm², cross section: 0.2 mm²- 6 mm², mounting type: NS 35/7,5, NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral The current is determined by the fuse used, the voltage by the selected LED.

If the fuse is faulty, the downstream circuit will not be disconnected.

Product propertiesProduct type Fuse terminal block

Area of application Railway industry

Machine building

Plant engineering

Number of connections 2

Number of rows 1

Potentials 1

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Fuse type Glass / ceramics / ...

Rated surge voltage 4 kV

Maximum power dissipation for nominal condition 1.02 W

Fuse G / 5 x 20

LED voltage range 12 V AC/DC ... 30 V AC/DC

LED current range 0.31 mA ... 0.95 mA

Maximum power dissipation max. 1.6 W (with single arrangement of the fuse terminal block in the event of overload)

max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)

max. 4 W (with single arrangement of the fuse terminal block in the event of a short-circuit)

max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)

Input data LED voltage range 12 V AC/DC ... 30 V AC/DC

Connection data Number of connections per level 2

Nominal cross section 4 mm²

Cross section AWG (converted acc. to IEC)

Stripping length 10 mm ... 12 mm

Internal cylindrical gage A4

Connection in acc. with standard IEC 60947-7-3

Conductor cross section rigid 0.2 mm² ... 6 mm²

Cross section AWG 24 ... 10 (converted acc. to IEC)

Conductor cross section flexible 0.2 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 4-HESILED 24 (5X20) BU/BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.