

## INDUSTRIAL COMPONENT DATA

# PT 4-HESILED 24 (5X20) RD/RD 1351436 PHOENIX CONTACT

## Fuse terminal block, fuse type: Glass/ceramic/..., fuse..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 4-HESILED 24 (5X20) RD/RD



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | PHOENIX CONTACT              |
| MPN / Reference | PT 4-HESILED 24 (5X20) RD/RD |
| Catalog number  | 1351436                      |
| Category        | Fuse terminal block          |
| Minimum order   | 50 Pcs                       |
| Document ID     | EO-DEDB20EB0A                |
| Generated       | 2026-08-05                   |

### Product Overview

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 24 V, nominal current: 6.3 A, connection type: Push-in connection, Sizing cross-section: 1 mm<sup>2</sup>, cross-section: 0.2 mm<sup>2</sup>- 6 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, colour: red

Fuse rail terminal, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, rated voltage: 24 V, rated current: 6.3 A, connection type: Push-in connection, 1st floor, Sizing section: 1 mm<sup>2</sup>, section: 0.2 mm<sup>2</sup>- 6 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, color: red

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

### Additional Product Information

ETIM for 1351436 Terminal blocks (EC000899)

Feature Name

Feature Value

Type of fuse insert (EF002530)

Other

Type of fuse holder (EF002531)

Other

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm<sup>2</sup>

Connectable conductor cross section solid-core (EF007337)

0.2 mm<sup>2</sup>

Rated current I<sub>n</sub> (EF008250)

6.3 A

Rated voltage (EF000228)

24 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of levels (EF002659)

1

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

6.15 mm

Height (EF000040)

55.9 mm

Depth (EF000049)

63.38 mm

Closing plate required (EF002525)

Yes

Colour (EF000007)

Red

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 4-HESILED 24 (5X20) RD/RD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.