

INDUSTRIAL COMPONENT DATA

PT 4-HESILED 24 (5X20) RD/RD 1351436 PHOENIX CONTACT

Fuse terminal block, fuse type: Glass/ceramic/..., fuse..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 4-HESILED 24 (5X20) RD/RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 4-HESILED 24 (5X20) RD/RD
Catalog number	1351436
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-DEDB20EB0A
Generated	2026-08-06

Product Overview

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 24 V, nominal current: 6.3 A, connection type: Push-in connection, Sizing cross-section: 1 mm², cross-section: 0.2 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, colour: red

Fuse rail terminal, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, rated voltage: 24 V, rated current: 6.3 A, connection type: Push-in connection, 1st floor, Sizing section: 1 mm², section: 0.2 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

ETIM for 1351436 Terminal blocks (EC000899)

Feature Name

Feature Value

Type of fuse insert (EF002530)

Other

Type of fuse holder (EF002531)

Other

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²
Connectable conductor cross section solid-core (EF007337)
0.2 mm²
Rated current I_n (EF008250)
6.3 A
Rated voltage (EF000228)
24 V
Type of electrical connection 1 (EF002526)
Other
Type of electrical connection 2 (EF002527)
Other
Number of levels (EF002659)
1
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
Material insulation body (EF007543)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Width (EF000008)
6.15 mm
Height (EF000040)
55.9 mm
Depth (EF000049)
63.38 mm
Closing plate required (EF002525)
Yes
Colour (EF000007)
Red

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 4-HESILED 24 (5X20) RD/RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.