

**INDUSTRIAL COMPONENT DATA**

# PT 6-DREHSELED 24 (5X20) 3025046 PHOENIX CONTACT

## Terminal rail for fuse, fuse type: Glass/ceramic/..., type ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 6-DREHSELED 24 (5X20)



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | PT 6-DREHSELED 24 (5X20) |
| Catalog number  | 3025046                  |
| Category        | Fuse terminal block      |
| Minimum order   | 25 Pcs                   |
| Document ID     | EO-FA797C9BA9            |
| Generated       | 2026-08-06               |

### Product Overview

Terminal rail for fuse, fuse type: Glass/ceramic/..., type of Connection: Connection push-in connection, section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 20 - 8, nominal current: 10 A, rated voltage: 1000 V, width: 12.3 mm, fuse type: G/5 x 20, class of mounting: NS 35/7,5, NS 35/15, color: black

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 24 V, nominal current: 10 A, connection type: Push-in connection, Dimensioning cross-section: 6 mm<sup>2</sup>, cross-section: 0.5 mm<sup>2</sup>- 10 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, colour: black

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

### Additional Product Information

ETIM for 3025046 Terminal blocks (EC000899)

Feature Name

Feature Value

Type of fuse insert (EF002530)

Other

Type of fuse holder (EF002531)

Other

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.5 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.5 mm<sup>2</sup>  
Connectable conductor cross section solid-core (EF007337)  
0.5 mm<sup>2</sup>  
Rated current I<sub>n</sub> (EF008250)  
10 A  
Rated voltage (EF000228)  
24 V  
Type of electrical connection 1 (EF002526)  
Other  
Type of electrical connection 2 (EF002527)  
Other  
Number of levels (EF002659)  
1  
Mounting method (EF000003)  
DIN rail (top hat rail) 35 mm  
Material insulation body (EF007543)  
Other  
Inflammability class of insulation material according to UL94 (EF002521)  
V0  
Width (EF000008)  
12.3 mm  
Height (EF000040)  
77.7 mm  
Depth (EF000049)  
49.841517 mm  
Closing plate required (EF002525)  
No  
Colour (EF000007)  
Black

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 6-DREHSEILED 24 (5X20) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.