


INDUSTRIAL COMPONENT DATA

PT-IQ-PTB-BE-UT 2905364 PHOENIX CONTACT Surge protection base element

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT-IQ-PTB-BE-UT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT-IQ-PTB-BE-UT
Catalog number	2905364
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-78E816A66B
Generated	2026-08-05

Product Overview

Surge protection base element

Base element for the PLUGTRAB PT-IQ-PTB remote supply and warning module...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 2905364

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356959506

Weight per Piece (excluding packing) 62.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Height 91.1 mm

Width 17.7 mm

Depth 51.5 mm

Horizontal pitch 1 Div.

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Altitude max. 4000 m (Above sea level)

Degree of protection IP20

General

Housing material PA 6.6

Flammability rating according to UL 94 V-0

Color black

Mounting type DIN rail: 35 mm

Type Base element, DIN rail mounting

Number of positions 1

Protective circuit

Nominal voltage UN 24 V DC

Operating voltage range 20 V DC ... 30 V DC

Rated current max. 130 mA (24 V DC)

max. 160 mA (20 V DC)

Max. required back-up fuse 500 mA (F)

Connection data

Connection method Screw connection

Screw thread M3

Tightening torque 0.5 Nm

Stripping length 8 mm

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section AWG 24 ... 12

Connection, equipotential bonding

Connection method DIN rail NS35

Standards and Regulations

Standards/specifications EN 61000-6-2 2005

EN 61000-6-3 2007

EN 61000-6-3 A1:2011

EN 60950-1 2006

EN 60950-1/A1 2010

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Classifications

eCl@ss 5.127130800eCl@ss 6.027130800eCl@ss 7.027130803eCl@ss 8.027130803eCl@ss 9.027130803

ETIM 4.0EC000941ETIM 5.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT-IQ-PTB-BE-UT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.