

INDUSTRIAL COMPONENT DATA

PT 2XEX(I)-24DC-ST 2838225 PHOENIX CONTACT Surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2XEX(I)-24DC-ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2XEX(I)-24DC-ST
Catalog number	2838225
Category	Combined arrester for data networks/MCR-technology
Minimum order	10 Pcs
Document ID	EO-063FE182E6
Generated	2026-07-31

Product Overview

Surge protection plug

PT plug-in protection protection circuit for two 2-conductor Ex i signal circuits driven free of ground potential. Nominal voltage: 24 V DC, suitable for HART.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 2838225

Packing unit 10 pc

Catalog page Page 132 (C-4-2017)

GTIN 4017918182861

Weight per Piece (excluding packing) 21.090 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 44.8 mm

Width 17.5 mm

Depth 51.7 mm

Horizontal pitch 1 Div.

Complete module height 90 mm
Complete module width 17.7 mm
Complete module depth 65.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Altitude ≤ 2000 m (amsl (above mean sea level))
Degree of protection IP20
General
Housing material PA 6.6
Flammability rating according to UL 94 V-0
Color sky blue RAL 5015
Mounting type on base element
Type Male
Number of positions 4
Direction of action Line-Line & Line-Signal Ground/Shield & Signal Ground/Shield-Earth Ground
Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.00
Protective circuit
IEC test classification C1
C2
C3
D1
Nominal voltage UN 24 V DC
Maximum continuous voltage UC 30 V DC
21 V AC
Rated current 325 mA (40 °C)
Operating effective current $I_{Cat UC} \leq 5 \mu A$
Residual current $I_{PE} \leq 4 \mu A$
Nominal discharge current $I_n(8/20) \mu s$ (line-line) 10 kA
Nominal discharge current $I_n(8/20) \mu s$ (line-earth) 10 kA
Pulse discharge current $I_{imp}(10/350) \mu s$ (line-line) 1 kA
Pulse discharge current $I_{imp}(10/350) \mu s$ (line-earth) 2 kA (in total)
Total discharge current $I_{total}(8/20) \mu s$ 20 kA
Total discharge current $I_{total}(10/350) \mu s$ 2 kA
Max. discharge current...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2XEX(I)-24DC-ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.