

INDUSTRIAL COMPONENT DATA

PTCB E1 24DC/0.1-0.63A NO 1441495 PHOENIX CONTACT

Protection of single-channel electronic equipment for cons..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTCB E1 24DC/0.1-0.63A NO



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTCB E1 24DC/0.1-0.63A NO
Catalog number	1441495
Category	Device circuit breaker
Minimum order	1 Pcs
Document ID	EO-317BBBE505
Generated	2026-08-02

Product Overview

Protection of single-channel electronic equipment for consumers of 12-24 V DC. Adjustable current rating from 0.1-0.63 A. With remote signal and active current limiting. Can be combined with CLIPLINE rail terminals. For installation on DIN rails. Electronic Appliance Protection Switches

Single-channel, electronic device protection for 12-24 V DC loads. Nominal current adjustable from 0.1-0.63 A. With remote signaling and active current limitation. Can be combined with CLIPLINE terminal blocks. For installation on DIN rails.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Over Current Protection

Additional Product Information

Technical dataNotesGeneral

Note Connection for signal line tested in accordance with EN 61000-4-4 with 1 kV; if necessary, customer must provide appropriate protective measures

Repeated hard short circuits can reduce the melting integral of the integrated backup fuse.

Product propertiesType DIN rail module, one-piece

Product type Device circuit breakers

Product family PTCB

Number of positions 1

No. of channels 1

Insulation characteristics

Protection class III

Pollution degree 2

Electrical properties No. of channels 1

General

Operating voltage 10 V DC ... 30 V DC

Rated voltage 24 V DC

Rated current IN 15 A DC (Total current input)

0.5 A DC (Rated current output)

Rated current IN 0.1 / 0.2 / 0.315 / 0.4 / 0.5 / 0.63 A DC (adjustable)

Rated current (pre-adjusted) 0.5 A

Rated surge voltage 0.5 kV

Tripping method E (electronic)

Feedback resistance max. 35 V DC

Required backup fuse Only required if I_{max} of the power supply > the short-circuit switching capacity. Integrated failsafe element.

Short-circuit switching capacity 300 A

Dielectric strength max. 35 V DC (Load circuit)

Active current limitation $\leq 1,2 \times I_N$, depending on the current setting

Fuse electronic

Efficiency > 98.5 %

Closed circuit current I_0 typ. 5 mA

Power dissipation typ. 0.1 W (No-load operation)

< 0.7 W (Nominal operation)

Module initialization time 40 ms

Waiting time after switch off of a channel 5 s (at overload / short circuit)

Measuring tolerance ± 17 % (Depending on the nominal current setting)

Temperature....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTCB E1 24DC/0.1-0.63A NO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.