

INDUSTRIAL COMPONENT DATA

MKKDS 1,5/ 2-5,08 GY 1702143 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDS 1,5/ 2-5,08 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDS 1,5/ 2-5,08 GY
Catalog number	1702143
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-1051B29C6E
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal block for printed circuit board, rated current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 1.5 mm², Number of rows: 2, Number of poles per row: 2, article family: MKKDS 1.5, pitch: 5.08 mm, connection type:Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0°, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1702143

Packing unit 1

GTIN 4046356572842

Custom tariff number 85369010

Item properties

Number of positions 2

Drive form screw head Slotted (L)

Screw thread M3

Pin layout Linear pinning

Dimensions for the product

Length [l] 21.4 mm
Width [w] 12.7 mm
Height [h] 29.5 mm
Pitch 5.08 mm
Height (without solder pin) 25.2 mm
Solder pin [P] 3.5 mm
Dimension a 5.08 mm
Dimensions for PCB design
Hole diameter 1.3 mm
Packaging information
Type of packaging packed in cardboard
Pieces per package 50
Denomination packing units Pcs.
Air clearances and creepage distances
Voltage 250 V
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss
7.027440401eCl@ss 8.027440401eCl@ss 9.027440401
ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643
UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC
13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDS 1,5/ 2-5,08 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.