

INDUSTRIAL COMPONENT DATA

PTDA 1,5/ 4-3,5 MIXED COLOR 1700903 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTDA 1,5/ 4-3,5 MIXED COLOR



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTDA 1,5/ 4-3,5 MIXED COLOR
Catalog number	1700903
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-E3FC36FB7F
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 240 V, nominal cross-section: 1.5 mm², number of rows: 1, number of poles per row: 4, article family: PTDA 1.5/, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: multicolor, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed

Printed circuit board terminal, nominal current: 17.5 A, rated voltage (III/2): 240 V, nominal cross section: 1.5 mm², number of rows: 1, number of positions per row: 4, product range: PTDA 1,5/, pitch: 3.5 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: multicolored, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 2, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family PTDA 1,5/

Product line COMBICON Terminals S

Number of positions 4

Pitch 3.5 mm

Number of rows 1

Pin layout Linear pinning
Solder pins per potential 2
Data management status
Article revision 02
Electrical propertiesNominal current IN 17.5 A
Nominal voltage UN 240 V
Rated voltage (III/3) 200 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 240 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 400 V
Rated surge voltage (II/2) 2.5 kV
Connection dataConnection technology
Nominal cross section 1.5 mm²
Conductor connection
Connection method Push-in spring connection
Conductor cross section rigid 0.2 mm² ... 1.5 mm²
Conductor cross section flexible 0.2 mm² ... 1.5 mm²
Conductor cross section AWG 24 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.5 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.5 mm² ... 0.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 0.5 mm²
Stripping length 10 mm
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)
Metal surface soldering area (top layer) Tin (4 - 8 µm....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTDA 1,5/ 4-3,5 MIXED COLOR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.