

INDUSTRIAL COMPONENT DATA

PTDA 2,5/ 3-5,0 BU 1672744 PHOENIX CONTACT Printed circuit board terminal, rated current: 24 A, rated voltag..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTDA 2,5/ 3-5,0 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTDA 2,5/ 3-5,0 BU
Catalog number	1672744
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-084ADF4285
Generated	2026-08-05

Product Overview

Printed circuit board terminal, rated current: 24 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of rows: 1, number of poles per row: 3, item family: PTDA 2.5/, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 45 °, color: blue, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1672744 Connectors (EC002643)

Feature Name

Feature Value

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type PCB (EF006822)

Soldering connection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTDA 2,5/ 3-5,0 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.