


INDUSTRIAL COMPONENT DATA

PTF 0,3/ 4-BB-8-H 1707559 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTF 0,3/ 4-BB-8-H



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTF 0,3/ 4-BB-8-H
Catalog number	1707559
Category	Cable connector
Minimum order	25 Pcs
Document ID	EO-57F9341D1C
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Direct connector for printed circuit board, nominal section: 0.34 mm², color: white, nominal voltage (III/2): 25 V, contact surface: Tin, contact connection type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: PTF 0.3/. -BB-H, pitch: 1.9 mm, mounting: Direct plug-in connection technology, plug-in system: COMBICON PTF, packaging type: box-packed, For flexible printed circuit boards with a width of 8 mm and a permissible printed circuit board thickness in the contact range of 0.15 mm ... 0.3 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1707559

Packing unit 25 pc

Minimum order quantity 25 pc

GTIN 4046356934237

Weight per Piece (excluding packing) 1.910 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [l] 8 mm

Width [w] 9.2 mm

Height [h] 4.8 mm

Pitch 1.9 mm

General

Range of articles PTF 0,3/...-BB-H

Number of positions 4

Insulating material group IIIa

Rated voltage (III/3) < 25 V

Rated voltage (III/2) 25 V

Nominal cross section 0.34 mm²

Maximum load current 10 A (Total current of all contacts)

Insulating material PBT

Flammability rating according to UL 94 V0

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 4.0EC002643ETIM 5.0EC002637ETIM 6.0EC002638

UNSPSC 13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTF 0,3/ 4-BB-8-H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.