


INDUSTRIAL COMPONENT DATA

PTFIX 10/18X4-G PK 3274049 PHOENIX CONTACT Block for distribution, bridged internally, rated voltage: 450 V,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 10/18X4-G PK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 10/18X4-G PK
Catalog number	3274049
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-61E4FFC7B2
Generated	2026-08-06

Product Overview

Block for distribution, bridged internally, rated voltage: 450 V, nominal current: 32 A, type of Connection: Connection push-in
Connection push-in connection, number of connections: 19, section: 0,2 mm²-6 mm², AWG: 24-10 width: 64,8 mm, height: 22,7 mm, color: pink, type of mounting: paste

Distribution block, internally bridged, nominal voltage: 450 V, nominal current: 32 A, number of connections: 19, connection type: Push-in connection, Branch, cross-section: 0.2 mm² - 6 mm², Push-in connection, Collective connection, Dimensioning cross-section: 10 mm², cross-section: 0.5 mm² - 10 mm², mounting type: glue, color: pink

Distribution block, bridged internally, nom. voltage: 450 V, nominal current: 32 A, number of connections: 19, connection method: Push-in connection, Load contact, cross section: 0.2 mm² - 6 mm², Push-in connection, Line contact, Rated cross section: 10 mm², cross section: 0.5 mm² - 10 mm², mounting type: adhesive, color: pink

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System
--------------	------------------------------------

Additional Product Information

Technical dataNotesGeneral

Note The maximum load current of a single clamping unit must not be exceeded.

For power distribution applications, IEC 60364-4-43:2008; modified + corrigendum Okt. 2008 (DIN VDE 0100-430:2010-10) section 433.2 ff must be observed!

Product propertiesProduct type Distributor terminal block

Number of connections 19

Number of rows 1

Potentials 1

Data management status

Article revision 01

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 6 kV

Maximum power dissipation for nominal condition 1.02 W

Connection data Service Entrance yes

Number of connections per level 19

Nominal cross section 4 mm²

Rated cross section AWG 6

Load contact

Stripping length 8 mm ... 10 mm

Internal cylindrical gage A3

Connection in acc. with standard IEC 60998-2-2

Conductor cross section rigid 0.2 mm² ... 6 mm²

Cross section AWG 24 ... 10 (converted acc. to IEC)

Conductor cross section flexible 0.2 mm² ... 4 mm²

Conductor cross section, flexible [AWG] 24 ... 12 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.2 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.2 mm² ... 4 mm²

Nominal current 32 A

Maximum load current 41 A

Maximum total current 63 A

Nominal voltage 450 V

Line contact

Stripping length 12 mm ... 14 mm

Connection in acc. with standard IEC 60998-2-2

Conductor cross section rigid 0.5 mm² ... 10 mm²

Cross section AWG 20 ... 6 (converte...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 10/18X4-G PK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.