


INDUSTRIAL COMPONENT DATA

PTFIX 10/18X4-NS35A YE 3273774 PHOENIX CONTACT Block for distribution, nominal voltage: 800 V, rated current..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 10/18X4-NS35A YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 10/18X4-NS35A YE
Catalog number	3273774
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-04D317D8D2
Generated	2026-08-02

Product Overview

Block for distribution, nominal voltage: 800 V, rated current: 32 A, type of Connection: Connection push-in Connection push-in connection, number of connections: 19, section: 0,2 mm²-6 mm², AWG: 24-10 width: 64,8 mm, color: yellow, type of mounting: NS 35/7,5, NS 35/15

Distribution block, nominal voltage: 800 V, nominal current: 32 A, number of connections: 19, connection type: Push-in connection, Branch, cross-section: 0.2 mm² - 6 mm², Push-in connection, Collective connection, Dimensioning cross-section: 10 mm², cross-section: 0.5 mm² - 10 mm², mounting class: NS 35/7.5, NS 35/15, colour: yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System
--------------	------------------------------------

Additional Product Information

Technical dataNotesGeneral

Observation The maximum charging current of the various terminal points must not be exceeded.

For applications for power distribution, IEC 60364-4-43:2008 must be observed, as amended + correction Oct. 2008 (DIN VDE 0100-430:2010-10) part 433.2 et seq.

Item PropertiesProduct Type Distribution terminal

Number of connections 19

Number of rows 1

Potential 1

Data Maintenance Status

Article Review 01

Insulation Properties

Surge Category Iii

Degree of pollution 3

Electrical Properties Dimensioning Transient Voltage 6 kV

Maximum Dissipated Power with Nominal Condition 1.02 W

Connection data Feeding Yes

Number of connections per floor 19

Nominal Section 4 mm²

AWG Sizing Section 10

Derivation

Peel Length 10 mm ... 12 mm

Male Gauge A4

Standard-compliant connection IEC 60947-7-1

Rigid conductor section 0.2 mm² ... 6 mm²

AWG Conductor Section 24 ... 10 (Converted according to IEC)

Flexible conductor section 0.2 mm² ... 4 mm²

Flexible Wire Section [AWG] 24 ... 12 (Converted according to IEC)

Flexible cable section (toe cap without plastic sleeve) 0.2 mm² ... 4 mm²

Flexible cable section (toe cap with plastic sleeve) 0.2 mm² ... 4 mm²

2 conductors with the same cross-section, flexible with TWIN toe cap with plastic sleeve 0.5 mm² ... 1 mm²

Nominal current 32 A

Maximum Charging Current 57 A

Maximum Sum Current 63 A

Nominal voltage 800 V

Collective connection

Peel Length 12 mm ... 14 mm

Standard-compliant connection IEC 60998-2-2

Rigid conductor section 0.5 mm²

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 10/18X4-NS35A YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.