

**INDUSTRIAL COMPONENT DATA**

# PTFIX 10/6X4 GY 3273856 PHOENIX CONTACT Block for distribution, rated voltage: 450 V, nominal current: 32 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 10/6X4 GY



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTFIX 10/6X4 GY             |
| Catalog number  | 3273856                     |
| Category        | Feed-through terminal block |
| Minimum order   | 8 Pcs                       |
| Document ID     | EO-B84196146C               |
| Generated       | 2026-08-03                  |

## Product Overview

Block for distribution, rated voltage: 450 V, nominal current: 32 A, type of Connection: Connection push-in Connection push-in connection, number of connections: 7, section: 0,2 mm<sup>2</sup>-6 mm<sup>2</sup>, AWG: 24-10, width: 27.9 mm, height: 21,7 mm, color: gray, assembly type: interlock adapter for rail

Distribution block, Base terminal with power, nominal voltage: 450 V, nominal current: 41 A, number of connections: 7, connection type: Push-in connection, Branch, Dimensioning section: 4 mm<sup>2</sup>, cross-section: 0.2 mm<sup>2</sup> - 6 mm<sup>2</sup>, Push-in connection, Collective connection, Dimensioning cross-section: 10 mm<sup>2</sup>, cross-section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting class: interlock in rail adapter, Direct mounting with a flange, Aerial, color: gray

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; FIX block System

## Additional Product Information

ETIM for 3273856 Terminal blocks (EC000897)

Feature Name

Feature Value

Rated current In (EF008250)

41 A

Rated voltage (EF000228)

450 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

7

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

27.9 mm

Height (EF000040)

28.6 mm

Depth (EF000049)

21.7 mm

Closing plate required (EF002525)

No

Colour (EF000007)

Grey

Internally connected stages (EF002661)

Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 10/6X4 GY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.