


## INDUSTRIAL COMPONENT DATA

# PTFIX 12X1,5 BU 3002763 PHOENIX CONTACT Distribution block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 12X1,5 BU



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTFIX 12X1,5 BU             |
| Catalog number  | 3002763                     |
| Category        | Feed-through terminal block |
| Minimum order   | 20 Pcs                      |
| Document ID     | EO-7CDE526E5A               |
| Generated       | 2026-08-05                  |

## Product Overview

Distribution block

Distribution block, internally bridged, rated voltage: 450 V, rated current: 17.5 A, number of connections: 12, connection type: Push-in connection, cross-section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting class: interlock in rail adapter, Direct mounting with a flange, Aerial, color: blue

Distribution block, bridged internally, nom. voltage: 450 V, nominal current: 17.5 A, number of connections: 12, connection method: Push-in connection, cross section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: blue

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                    |
|--------------|------------------------------------|
| Catalog path | PHOENIX CONTACT > FIX block System |
|--------------|------------------------------------|

## Additional Product Information

Technical dataNotesNotes on operation the blocks can be bridged with one another via the conductor shaft, for corresponding plug-in bridges, see accessories

Product propertiesProduct type Distributor terminal block

Number of connections 12

Number of rows 1

Potentials 1

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III  
Degree of pollution 3  
Electrical properties Rated surge voltage 6 kV  
Maximum power dissipation for nominal condition 0.56 W  
Connection data Number of connections per level 12  
Nominal cross section 1.5 mm<sup>2</sup>  
Rated cross section AWG 14  
Stripping length 8 mm ... 10 mm  
Internal cylindrical gage A1 / B1  
Connection in acc. with standard IEC 60998-2-2  
Conductor cross section rigid 0.14 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Cross section AWG 26 ... 14 (converted acc. to IEC)  
Conductor cross section flexible 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section, flexible [AWG] 26 ... 16 (converted acc. to IEC)  
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Nominal current 17.5 A  
Maximum load current 22 A  
Maximum total current 26 A  
Nominal voltage 450 V  
Connection cross sections directly pluggable  
Conductor cross section rigid 0.34 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section, rigid [AWG] 26 ... 14 (converted acc. to IEC)  
Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Flexible conductor cross section (fer...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 12X1,5 BU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.