

INDUSTRIAL COMPONENT DATA

MK3DSH 3/ 9-5,08 BU BD:1-9 1707588 PHOENIX CONTACT

Terminal block for printed circuit board, rated current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MK3DSH 3/ 9-5,08 BU BD:1-9



Manufacturer	PHOENIX CONTACT
MPN / Reference	MK3DSH 3/ 9-5,08 BU BD:1-9
Catalog number	1707588
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-5AEDD6C8A3
Generated	2026-08-05

Product Overview

Terminal block for printed circuit board, rated current: 24 A, rated voltage: 400 V, pitch: 5.08 mm, number of poles: 9, connection type: Screw connection with traction capsule, mounting: Wave soldering, connection direction conductor/printed circuit board: 0 °, color: blue

Terminal block for printed circuit board, rated current: 24 A, rated voltage (III/2): 400 V, nominal section: 2.5 mm², number of rows: 1, number of poles per row: 9, article family: MK3DSH 3, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping shape: L Longitudinal slot, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Blue, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 5mm, Number of Soldering Pins per Potential: 1, Packaging Type: Boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 9, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: blue
Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsTall type enables conductor connection for sealed PCBsConductor connection on several levels enables higher contact densityIntegrated protective guide prevents incorrect insertion of the conductor underneath the tension sleeveThe latching on the side enables various numbers of positions to be combinedKey Commercial Data
Orderkey 1707588

Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356935272
Weight per Piece (excluding packing) 30.770 g
Custom tariff number 85369010
Country of origin DE (Germany)
Material data - housing
Housing color blue (5015)
Dimensions for the product
Length [l] 12.1 mm
Width [w] 45.72 mm
Height (without solder pin) 44.8 mm
Solder pin [P] 5 mm
Dimension a 40.64 mm
Dimensions for PCB design
Hole diameter 1.3 mm
Packaging information
Type of packaging packed in cardboard
Pieces per package 50
Denomination packing units Pcs.
Air clearances and creepage distances
Voltage 250 V
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Environmental Product Compliance
China RoHS Environmentally Friendly Use Pe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MK3DSH 3/ 9-5,08 BU BD:1-9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.