

**INDUSTRIAL COMPONENT DATA**

# PTFIX 1,5-KNX-NS35 1187192 PHOENIX CONTACT Function distributor block, for KXN bus in building installation,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 1,5-KNX-NS35



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTFIX 1,5-KNX-NS35          |
| Catalog number  | 1187192                     |
| Category        | Feed-through terminal block |
| Minimum order   | 10 Pcs                      |
| Document ID     | EO-53463E59BF               |
| Generated       | 2026-08-05                  |

## Product Overview

Function distributor block, for KXN bus in building installation, the individual block is internally bridged, color according to EIB cable coding, layout: Inline, rated voltage: 500 V, rated current: 17.5 A, number of connections: 24, connection type: Push-in connection, cross-section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting class: NS 15, NS 35/7.5, NS 35/15

Block for distribution, for KXN bus in installation in buildings, the individual block is internally bridged, color according to EIB cable coding, arrangement: Inline, nominal voltage: 500 V, nominal current: 17.5 A, connection type: Push-in connection, number of connections: 24, section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 26 - 14, width: 21.6 mm, height: 24.4 mm, Mounting class: NS 15, NS 35/7.5, NS 35/15

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; FIX block System

## Additional Product Information

ETIM for 1187192 Terminal blocks (EC000897)

Feature Name

Feature Value

Rated current In (EF008250)

17.5 A

Rated voltage (EF000228)

500 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

24

Mounting method (EF000003)

DIN rail (top hat rail) 15 mm

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

21.6 mm

Height (EF000040)

58.1 mm

Depth (EF000049)

24.4 mm

Closing plate required (EF002525)

No

Colour (EF000007)

Multi colour

Internally connected stages (EF002661)

Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 1,5-KNX-NS35 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.