


INDUSTRIAL COMPONENT DATA

PTFIX 18X2,5 GN 3273316 PHOENIX CONTACT Distribution block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 18X2,5 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 18X2,5 GN
Catalog number	3273316
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-BEDC4E29A3
Generated	2026-08-05

Product Overview

Distribution block

Distribution block, Base terminal, rated voltage: 450 V, rated current: 24 A, number of connections: 18, connection type: Push-in connection, cross-section: 0.14 mm² - 4 mm², mounting class: interlock in rail adapter, Direct mounting with a flange, Aerial, color: green

Distribution block, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 18, connection method: Push-in connection, cross section: 0.14 mm² - 4 mm², mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System
--------------	------------------------------------

Additional Product Information

Technical dataNotesNotes on operation the blocks can be bridged with one another via the conductor shaft, for corresponding plug-in bridges, see accessories

General

Note The maximum load current of a single clamping unit must not be exceeded.

Product propertiesProduct type Distributor terminal block

Number of connections 18

Number of rows 1

Potentials 1

Data management status

Article revision 03
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical properties Rated surge voltage 6 kV
Maximum power dissipation for nominal condition 0.77 W
Connection data Number of connections per level 18
Nominal cross section 2.5 mm²
Rated cross section AWG 12
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A3
Connection in acc. with standard IEC 60998-2-2
Conductor cross section rigid 0.14 mm² ... 4 mm²
Cross section AWG 26 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section, flexible [AWG] 26 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
Nominal current 24 A
Maximum load current 32 A
Maximum total current 48 A
Nominal voltage 450 V
Connection cross sections directly pluggable
Conductor cross section rigid 0.34 mm² ... 4 mm²
Conductor cross section, rigid [AWG] 24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 18X2,5 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.