


INDUSTRIAL COMPONENT DATA

PTFIX 18X4-FE-G 3273986 PHOENIX CONTACT Distribution block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 18X4-FE-G



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 18X4-FE-G
Catalog number	3273986
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-B9D2DD6864
Generated	2026-07-31

Product Overview

Distribution block

Distribution block, internally bridged, nominal voltage: 450 V, nominal current: 32 A, number of connections: 18, connection type: Push-in connection, cross-section: 0.2 mm² - 6 mm², mounting type: glue, color: black/yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > FIX block System

Additional Product Information

Key Commercial Data

Orderkey 3273986

Packing unit 8 pc

Minimum order quantity 8 pc

Note Made to Order (non-returnable)

GTIN 4055626647395

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note Notes on operation The blocks can be bridged with one another via the conductor shaft. For corresponding plug-in bridges, see accessories

Number of levels 1

Number of connections 18

Potentials 1

Nominal cross section 4 mm²

Color black/yellow

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W (the value is based on one connection block and is multiplied according to the pin assignment)

Ambient temperature (operation) -60 °C ... 130 °C

Maximum load current 63 A

Nominal current I_N 32 A

Nominal voltage U_N 450 V

Open side panel No

Dimensions

Width 55.4 mm

Length 28.6 mm

Height 22.7 mm

Connection data

Connection method Push-in connection

Connection in acc. with standard IEC 60998-2-2

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 12

Conductor cross section flexible, with ferrule w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 18X4-FE-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.