

INDUSTRIAL COMPONENT DATA

PTFIX 2X1,5 TQ 1082538 PHOENIX CONTACT Block for distribution, Terminal base, rated voltage: 450 V, rated cu..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 2X1,5 TQ



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 2X1,5 TQ
Catalog number	1082538
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-CB979FB3ED
Generated	2026-08-05

Product Overview

Block for distribution, Terminal base, rated voltage: 450 V, rated current: 17,5 A, type of Connection: Connection push-in connection, number of connections: 2, section: 0.14 mm²-2.5 mm², AWG: 26-14, width: 4.2 mm, height: 17.7 mm, color: turquoise, type of mounting: latch on adapter for rail

Distribution block, Base terminal, nominal voltage: 450 V, nominal current: 17.5 A, number of connections: 2, connection type: Push-in connection, cross-section: 0.14 mm² - 2.5 mm², mounting type: interlock in rail adapter, Direct mounting with a flange, Aerial, color: turquoise

Monoblock, Basic terminal block, nom. voltage: 450 V, nominal current: 17.5 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm² - 2.5 mm², mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: turquoise

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System
--------------	------------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Distributor terminal block

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 01

Insulation characteristics

Overvoltage category III
Degree of pollution 3
Electrical properties Rated surge voltage 6 kV
Maximum power dissipation for nominal condition 0.56 W
Connection data Number of connections per level 2
Nominal cross section 1.5 mm²
Rated cross section AWG 14
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A1 / B1
Connection in acc. with standard IEC 60998-2-2
Conductor cross section rigid 0.14 mm² ... 2.5 mm²
Cross section AWG 26 ... 14 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG] 26 ... 16 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 1.5 mm²
Nominal current 17.5 A
Maximum load current 21 A (with a 2.5 mm² conductor cross section)
Maximum total current 21 A
Nominal voltage 450 V
Connection cross sections directly pluggable
Conductor cross section rigid 0.34 mm² ... 2.5 mm²
Conductor cross section, rigid [AWG] 26 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.34 mm² ... 1.5 mm²
Dimensions Width 4.2 mm
Height 21.6 mm
Depth 17.7 mm
Mater...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 2X1,5 TQ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.