

INDUSTRIAL COMPONENT DATA

PTFIX 6/12X2,5 BUWH 1091672 PHOENIX CONTACT Block for distribution, Terminal base with power, The blocks can..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 6/12X2,5 BUWH



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 6/12X2,5 BUWH
Catalog number	1091672
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-A775F1AEA7
Generated	2026-08-03

Product Overview

Block for distribution, Terminal base with power, The blocks can be bridging between themselves by the channel drivers. Bridges plug-in adapted, see accessories, rated voltage: 450 V, nominal current: 24 A, type of Connection: Connection push-in Connection push-in connection, number of connections: 13, section: 0.14 mm²-4 mm², AWG: 26-12, width: 41 mm, height: 21,7 mm, color: blue/white, assembly type: interlock adapter rail, adapter Plate

Distribution block, Base terminal with power, nominal voltage: 450 V, nominal current: 24 A, number of connections: 13, connection type: Push-in connection, Branch, cross-section: 0.14 mm² - 4 mm², Push-in connection, Collective connection, Dimensioning cross-section: 6 mm², cross-section: 0.5 mm² - 10 mm², mounting class: interlock in rail adapter, Direct mounting with a flange, Aerial color: blue/white

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System
--------------	------------------------------------

Additional Product Information

ETIM for 1091672 Terminal blocks (EC000897)

Feature Name

Feature Value

Rated current In (EF008250)

24 A

Rated voltage (EF000228)

450 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

13

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

41 mm

Height (EF000040)

28.6 mm

Depth (EF000049)

21.7 mm

Closing plate required (EF002525)

No

Colour (EF000007)

Multi colour

Internally connected stages (EF002661)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 6/12X2,5 BUWH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.