

INDUSTRIAL COMPONENT DATA

PTFIX 6/6X2,5-MTL 1130760 PHOENIX CONTACT Function distributor block, Base terminal with power supply and di..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 6/6X2,5-MTL



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 6/6X2,5-MTL
Catalog number	1130760
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-CAE2EFECD8
Generated	2026-08-03

Product Overview

Function distributor block, Base terminal with power supply and disconnecter blade in the branches, separation with screwdriver or by hand, nominal voltage: 400 V, nominal current: 20 A, Derivation, connection type: Push-in connection, Dimensioning section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², Collective connection, connection type: Push-in connection, Dimensioning section: 6 mm², cross-section: 0.5 mm² - 10 mm², mounting: interlock in rail adapter, Direct mounting with a flange, Aerial, colour: grey

Distribution block, Base terminal with power and sectioning blade in the branches, separation with screwdriver or by hand, nominal voltage: 400 V, nominal current: 20 A, Attack floor, connection type: Push-in connection, Dimensioning section: 2.5 mm², section: 0.14 mm² - 4 mm², Power plant, Sizing section: 6 mm², section: 0.5 mm² - 10 mm², mounting: nailing to rail adapter, Direct mounting with a flange, Aerial, color: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > FIX block System

Additional Product Information

ETIM for 1130760 Terminal blocks (EC000897)

Feature Name

Feature Value

Rated current In (EF008250)

20 A

Rated voltage (EF000228)

400 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

7

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

47.6 mm

Height (EF000040)

28.6 mm

Depth (EF000049)

28.2 mm

Closing plate required (EF002525)

No

Colour (EF000007)

Grey

Internally connected stages (EF002661)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 6/6X2,5-MTL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.