


**INDUSTRIAL COMPONENT DATA**

# PTFIX 6/6X2,5-NS35A WH 3273210 PHOENIX CONTACT

## Verteilerblock

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 6/6X2,5-NS35A WH



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTFIX 6/6X2,5-NS35A WH      |
| Catalog number  | 3273210                     |
| Category        | Feed-through terminal block |
| Minimum order   | 10 Pcs                      |
| Document ID     | EO-79AF9F81CC               |
| Generated       | 2026-08-05                  |

### Product Overview

**Verteilerblock**

Distribution block, Block with horizontal alignment and integrated power supply, nominal voltage: 690 V, nominal current: 41 A, number of connections: 7, connection type: Push-in connection, Collective connection, Dimensioning section: 6 mm<sup>2</sup>, section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, Push-in connection, Branch, section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, color: white

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; FIX block System

### Additional Product Information

**Key Commercial Data**

Orderkey 3273210

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 145 (C-1-2017)

GTIN 4055626391670

Weight per Piece (excluding packing) 22.630 g

Custom tariff number 85369010

Country of origin PL (Poland)

**General**

Note Notes on operation The blocks can be bridged with one another via the conductor shaft. For corresponding plug-in

bridges, see accessories

Number of levels 1

Number of connections 7

Potentials 1

Nominal cross section 2.5 mm<sup>2</sup>

Nominal cross section feed-in 6 mm<sup>2</sup>

Color white

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.31 W (the value is based on one connection block and is multiplied according to the pin assignment)

Maximum load current 32 A (with 4 mm<sup>2</sup> conductor cross section)

Maximum total current 57 A (with 10 mm<sup>2</sup> conductor cross section)

Nominal current IN 24 A

Nominal voltage UN 690 V

Maximum load current 57 A (with 10 mm<sup>2</sup> conductor cross section)

Nominal current IN 41 A (with 6 mm<sup>2</sup> conductor cross section)

Open side panel No

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 9.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.89 kV

Result...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 6/6X2,5-NS35A WH with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.