

INDUSTRIAL COMPONENT DATA

PTFIX 6/6X2,5-TG 1130751 PHOENIX CONTACT Function distributor block, Current and voltage are determined by t..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 6/6X2,5-TG



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 6/6X2,5-TG
Catalog number	1130751
Category	(Knife) disconnect terminal block
Minimum order	8 Pcs
Document ID	EO-A316B0F6C5
Generated	2026-08-05

Product Overview

Function distributor block, Current and voltage are determined by the connector used., Base terminal with power supply and multifunctional interrupting area in the branches, nominal voltage: 400 V, nominal current: 20 A, Shunt, connection type: Push-in connection, Dimensioning section: 2.5 mm², section: 0.14 mm² - 4 mm², Collective connection, connection type: Push-in connection, Sizing cross-section: 6 mm², cross-section: 0.5 mm² - 10 mm², Mounting: interlock on rail adapter, Direct mounting with a flange, Aerial, color: gray

Distribution block, Base terminal with power supply and multifunctional interrupt zone in the branches, nominal voltage: 400 V, nominal current: 20 A, Attack floor, connection type: Push-in connection, Dimensioning section: 2.5 mm², section: 0.14 mm² - 4 mm², Power plant, Dimensioning section: 6 mm², section: 0.5 mm² - 10 mm², mounting: nail in rail adapter, Direct mounting with a flange, Aerial, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > FIX block System

Additional Product Information

ETIM for 1130751 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Rated current I_n (EF008250)

20 A

Rated voltage (EF000228)

400 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

7

Internally connected stages (EF002661)

Yes

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

47.6 mm

Height (EF000040)

28.6 mm

Depth (EF000049)

21.7 mm

Closing plate required (EF002525)

No

Colour (EF000007)

Grey

Type of cross disconnection (EF002546)

None

With integrated test socket (EF002547)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 6/6X2,5-TG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.