

INDUSTRIAL COMPONENT DATA

PTFIX-NS35 LQ 1092937 PHOENIX CONTACT Adapter for rail, length: to the tune of 58.1 mm, width: 28.6 mm, heig..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX-NS35 LQ



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX-NS35 LQ
Catalog number	1092937
Category	DIN-rail adapter
Minimum order	200 Pcs
Document ID	EO-B79271F7E1
Generated	2026-08-06

Product Overview

Adapter for rail, length: to the tune of 58.1 mm, width: 28.6 mm, height: 11 mm, color: gray

Rail adapter, Rail adapters, larger packaging unit, length: 58.1 mm, width: 28.6 mm, height: 11 mm, color: gray, mounting class: NS 35/7.5

DIN rail adapter, DIN rail adapter, larger packing unit, depth: 11 mm, width: 28.6 mm, height: 58.1 mm, color: gray, mounting type: NS 35/7,5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System
--------------	------------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Mounting material

Data management status

Article revision 00

DimensionsWidth 28.6 mm

Height 58.1 mm

Depth 11 mm

Depth on NS 35/7,5 15 mm

Depth on NS 35/15 22.5 mm

Material specificationsColor gray (RAL 7042)

Material PA

Flammability rating according to UL 94 V0

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (storage/transport) 30 % ... 70 %

Mounting Mounting type NS 35/7,5

NS 35/15

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX-NS35 LQ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.